

Page: 1 Revised edition no: 6 Date: 6 / 1 / 2014

Supersedes: 0/0/0

Gulf Harmony AW 32

10103/32/1/6

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier Gulf Harmony AW 32

Viscosity Grade ISO VG 32 **Product code Gulf Oil International** 10103/32/1/6

Relevant identified uses of the

substance or mixture and uses advised against

Details of the supplier of the safety

data sheet

Industrial hydraulic oil.

This oil should not be used for any other purpose than the intended use as a hydraulic oil

without expert advice.

: Gulf Oil Lubricants India Ltd, IN Centre, 12th Road, Marol,

Andheri (East), Mumbai - 400 093

: +91 22 66487777 **Emergency telephone number**

HAZARDS IDENTIFICATION

Classification of the substance or

mixture

: Combustible liquid.

Most important adverse physico-

chemical effects

Most important adverse human health

Prolonged or repeated skin contact with the material will remove natural oils and could lead to

: Not classified as dangerous under EC criteria.

a dermatitis.

Most important adverse environmental: No specific risk for the environment.

effects

Label elements:

- safety advices : Do not empty into drains; dispose of this material and its container in a safe way.

Other hazards Injection under the skin can occur when using high pressure equipment. Overexposure to oil

mist may cause respiratory irritations.

Oil mist deposited on surfaces may cause slip hazard.

COMPOSITION/INFORMATION ON INGREDIENTS 3.

Chemical characterization : Mixture of highly refined mineral oils and additives.(PCA-content < 3% - IP 346)

Substance name		Contents	CAS No	EC No	Annex No	Ref REACH	Classification
Zinc dialkyl dithiophosphate	:	0.36 - 0.66 %	68649-42-3	272-028-3			Xi; R36/38
Alkyl phenol	:	0.11 - 0.22 %					N; R50-53
Long chain alkenyl succinimide	:	0.06 - 0.11 %					
Calcium alkaryl sulfonate	:	0.006 - 0.011 %					Xi; R38-41
Aryl phosphine	:	0.0029 - 0.0055 %					Xn; R48/20/22 R43 N: R50-53

FIRST AID MEASURES

Description of first aid measures:

- after inhalation : Assure fresh air breathing. If you feel unwell, seek medical advice.

Remove contaminated clothing and shoes. Wash skin thoroughly with mild soap and water. - after contact with skin

Never use kerosine or gasoline for cleaning the skin.

- after contact with the eyes Rinse immediately with plenty of water. Seek medical attention if irritation develops.

- after ingestion Do not induce vomiting. Seek medical attention immediately.

- after injection If injected under the skin when using high pressure equipment, send casualty immediately to

a hospital, even when there are few or no symptoms.

Gulf Oil International

16 Charles II St. SW1Y 4QU - London - United



Page: 2 Revised edition no: 6 Date: 6 / 1 / 2014

Supersedes: 0/0/0

Gulf Harmony AW 32

10103/32/1/6

SECTION 4. FIRST AID MEASURES (continued)

both acute and delayed

idication of any immediate medical attention and special treatment needed

Most important symptoms and effects,: Symptoms of overexposure to vapours include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision.

> High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. Often these injuries require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of the injury.

FIRE-FIGHTING MEASURES

Suitable extinguishing media

Extinguishing media which shall not

be used for safety reasons

substance or mixture

Special hazards arising from the

Advice for firefighters

: Water fog. Carbon dioxide. Foam. Dry chemical product.

Do not use a heavy water stream.

Under fire conditions, hazardous fumes will be present.

Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus, rubber boots and thick rubber gloves. Use water

spray or fog for cooling exposed containers. Avoid fire-fighting water to enter environment.

ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

- for non-emergency personnel

: Evacuate unnecessary personnel.

- for emergency responders **Environmental precautions**

Equip cleanup crew with proper protection. Wear suitable protective clothing, gloves and eye Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams. Avoid release to the environment. Notify authorities if liquid enters sewers or public

or face protection. Eliminate every possible source of ignition.

Methods and material for containment and cleaning up

waters. Spill area may be slippery. Clean up any spills as soon as possible, using an absorbent material to collect it

Use suitable disposal containers.

Reference to other sections

: See Heading 8 & 13

HANDLING AND STORAGE

Precautions for safe handling

Keep away from sources of ignition. No naked lights. No smoking. Use only in well ventilated areas. Avoid release to the environment. Do no eat, drink or smoke when using this product.

Wash hands and other exposed areas with soap and water before leaving work.

Conditions for safe storage, including :

any incompatibilities

Store this product in a dry location where it can be protected from the elements.

Store in tightly closed, properly ventilated containers away from heat, sparks, open flame,

strong oxidizers, radiations, and other initiators. Keep at temperature not exceeding 50℃.

Industrial hydraulic oil. Specific end use(s)

This oil should not be used for any other purpose than the intended use as a hydraulic oil

without expert advice.



Page: 3 Revised edition no: 6 Date: 6 / 1 / 2014

Supersedes: 0/0/0

Gulf Harmony AW 32

10103/32/1/6

EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters:

Occupational exposure limit values:

- Australia National exposure standards for atmosperic contaminants in the occupational environment;

Time-Weighted Average (normal eight-hour working day, for a five-day working week): 5 mg/ m³ for oil mist, refined mineral. (National Occupational Health & Safety Commission [NOHSC:

1003(1995)]

- Canada The American Conference of Governmental Industrial Hygienists (ACGIH) has assigned

mineral oil mist a threshold limit value (TLV) of 5 mg/m(3) as a Time Weighted Average (TWA) for a normal 8-hour workday and a 40-hour workweek and a short-term exposure limit (STEL) of 10 mg/m(3) for periods not to exceed 15 minutes. Exposures at the STEL

concentration should not be repeated more than four times a day and should be separated by

intervals of at least 60 minutes.

[ACGIH 1994, p. 28]

- EU Occupational Exposure Standard (OES) of 5 mg/m³,

8-hour time-weighted average reference period for oil mist.

The American Conference of Governmental Industrial Hygienists (ACGIH) has assigned - USA

mineral oil mist a threshold limit value (TLV) of 5 mg/m(3) as a Time Weighted Average (TWA) for a normal 8-hour workday and a 40-hour workweek and a short-term exposure limit (STEL) of 10 mg/m(3) for periods not to exceed 15 minutes. Exposures at the STEL

concentration should not be repeated more than four times a day and should be separated by

intervals of at least 60 minutes.

[ACGIH 1994, p. 28]

Occupational Exposure Limits

: No data available. **Biological limit values**

Exposure controls:

Individual protection measures, such as personal protective equipment:

- eye / face protection : Chemical goggles or safety glasses (EN 166)

: Wear suitable protective clothing. - skin protection

Wear suitable gloves resistant to chemical penetration. (EN 374) - hand protection

The use of Filtertype A (EN 141) is recommended If exceeding the Occupational Exposure - respiratory protection

Limit.

Do not wear leather soled shoes. **Environmental exposure controls** Avoid release to the environment.

PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties:

- physical state Oily liquid. - colour Yellow-brown.

- odour Light odour of petroleum.

- flash point 202℃ - density @ 15℃ : 870 kg/m³ - solubility in water : Insoluble. - viscosity @ 40℃ 31.2 cSt - pour point -24°C

Other information See Product Data Sheet for detailed information.



Page: 4 Revised edition no: 6 Date: 6 / 1 / 2014

Supersedes: 0/0/0

Gulf Harmony AW 32

10103/32/1/6

STABILITY AND REACTIVITY

Reactivity No data available.

Chemical stability Stable under normal conditions. Possibility of hazardous reactions None under normal conditions. Conditions to avoid Extremely high or low temperatures.

Incompatible materials Strong oxidizing agents. Hazardous decomposition products None under normal conditions.

TOXICOLOGICAL INFORMATION

Information on toxicological effects:

- acute toxicity : No specific toxicity data on this product available. Not expected to be an irritant to eyes or skin. - irritation

Inhalation of fumes or vapours may cause respiratory irritation.

- corrosivity : No adverse health effects were noted. - sensitisation No sensitization effects known.

- carcinogenicity This product contains mineral oils which are considered to be severely refined and not

considered to be carcinogenic under IARC. All of the oils in this product have been

demonstrated to contain less than 3% extractables by the IP 346 test.

: Not expected to be mutagenetic. - mutagenicity

- reproductive toxicity Not expected to be toxic.

Information on likely routes of exposure:

Ingestion may cause nausea, vomiting and diarrhoea. - after ingestion - after inhalation Inhalation of vapours may cause respiratory irritation.

Prolonged or repeated skin contact with the material will remove natural oils and could lead to - after skincontact

a dermatitis.

 after eyecontact Slight eye irritant upon direct contact. Symptoms related to the physical, No adverse health effects were noted.

chemical and toxicological

characteristics

Delayed and immediate effects as well : as chronic effects from short and long-

term exposure

No adverse health effects were noted

Other toxicological information : No data available.

ECOLOGICAL INFORMATION

No specific ecotoxicity data on this product available. **Toxicity**

Not determined. Persistence and degradability Bioaccumulative potential No data available.

It is to be expected small mobility in soil. Some or a few components may get into the soil and Mobility in soil

may cause pollution of ground water. Product spreads on the water surface.

Results of PBT and vPvB assessment : Not applicable.

Other adverse effects : May contaminate water supplies.

Biodegradation : No data available.



Page: 5 Revised edition no: 6 Date: 6 / 1 / 2014

Supersedes: 0/0/0

Gulf Harmony AW 32

10103/32/1/6

DISPOSAL CONSIDERATIONS

Waste Disposal : Dispose in a safe manner in accordance with local/national regulations.

Waste treatment methods See Directive 2001/118/EC

13 02 05 - mineral-based non-chlorinated engine, gear and lubricating oils. Waste Code European Waste List

15 01 10 - packaging containing residues of or contaminated by dangerous substances.

TRANSPORT INFORMATION 14.

Not regulated.

REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Australian Inventory of Chemical

Substances (AICS) - Canadian Environmental Protection : All components are in compliance with chemical notification requirements in Australia.

All components are in compliance with the Canadian Environmental Protection Act (CEPA) and are present on the Domestic Substances List (DSL).

Act (CEPA) - European Inventory of Existing

Commercial Chemical Substances (EINECS)

: All components listed.

- USA Toxic Substances Control Act

(TSCA)

: All components of this material are on the US TSCA Inventory or are exempt.

- Germany : Water Hazard Class: 1 - low hazard to waters

OTHER INFORMATION

Revision Indicators None.

Key to abbreviations and acronyms used in the safety data sheet

ACGIH = American Conference of Industrial Hygienists

CLP = Classification and Labelling of Substances and Preparations

EC = European Commission. EN = European Norm IARC= International Agency for Research on Cancer

IP = Institute of Petroleum. ISO = International Organization for Standardization

NLGI = National Lubricating Grease Institute

PCA = Polycyclic Aromatics

TLV = Threshold Limit Value. TWA = Time Weighted Average

VG = Viscosity Grade

for data

Key literature references and sources : Concawe Report 01/53, Concawe Report 01/54, Concawe Report 05/87.

Regulations (EC) No 1907/2006, 1272/2008 & 453/2010 of the European Parliament and of

the Council.

List of relevant R-phrases R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitization by skin contact.

R48/20/22: Harmful: danger of serious damage to health by prolonged exposure through

inhalation and if swallowed.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

Training advice : See information supplied by the manufacturer.

The contents and format of this SDS are in accordance with COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this

Gulf Oil International

16 Charles II St. SW1Y 4QU - London - United Kingdom



Page: 6 Revised edition no : 6 Date: 6 / 1 / 2014 Supersedes: 0/0/0

Gulf Harmony AW 32

10103/32/1/6

product. If the product is used as a component in another product, this SDS information may not be applicable.

End of document