MATERIAL SAFETY DATA SHEET

Page 1 of 10

MSDS-062G

Пор	died to OSHA, ACC, ANSI, NORSC, WHMIS, 2001/38/EC & 12/2/2008/EC Standards MSDS Revision: 4.0 MSDS Revision Date: 08/23/2011						
	1 DODUCT IDENTIFICATION						
	1. PRODUCT IDENTIFICATION						
1/1	Product Name:						
	OPI NAIL LACQUER						
1.2	Chemical Name:						
	SOLVENT MIXTURE						
1.3	Synonyms:						
	NA						
1.4	Trade Names: NL**** (Various Colors)						
1.5	Product Use: COSMETIC USE ONLY						
1.6	Manufacturer's Name:						
	OPI PRODUCTS, INC.						
1.7	Manufacturer's Address;						
	13034 SATICOY STREET, NO. HOLLYWOOD, CA 91605 USA						
1.8	Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300						
1.9	Business Phone:						
	+1 (818) 759-2400 / +1 (800)-341-9999						
	2. IDENTIFICATION OF RISKS						
2.1	Hazard Identification:						
	This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the						
	classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). Flammable liquid.						
	Hazard Statements: H225 Highly flammable liquid and vapor. H319 Causes Serious Eye Irritation.						
	Precautionary Statements: P210Keep away from heat/sparks/open flames/hot surfaces — No Smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if						
	present and easy to do. Continue rinsing.						
	HAZCHEM CODE: 3YE						
2.0	Poison Schedule: None Allocated.						
2.2	Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES						
2.3	Effects of Exposure:						
	INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.						
	SKIN & EYES: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.						
	INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system.						
	Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of						
	vapors exceeding the levels listed in Section 2 (Composition and Ingredient Information) can cause central nervous						
2.4	system depression (e.g., drowsiness, dizziness, headaches, nausea). Symptoms of Overexposure:						
2.7	Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes						
	may cause redness, itching and watering.						
2.5	Acute Health Effects:						
	Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.						
2.6	Chronic Health Effects:						
	None known.						
2.7	Target Organs:						
	Eyes, skin and respiratory system.						
	Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used						
NOTE	: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2010 format.						

MATERIAL SAFETY DATA SHEET

Page 2 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

l l							EVP	CIIDE ''					
					ACGIH NOHSC				AIR (
					pp		-	ppm	•	-	OSHA ppm		OTHE
							ES-	ES-	ES-				OTTIL
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	400
ETHYL ACETATE	141-78-6	AH5425000	201-550-6	> 25.0	400	400	200	400	NF	NA	NA	2000	TWA
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	> 24 .0	150	200	150	200	NF	200	200	1700	150 TWA
NITROCELLULOSE	9004-70-0	QW0970000	NA	> 12.0	(10)	NE	NF	NF	NF	(10)	NE	NE	
PROPYL ACETATE	109-60-4	AJ3675000	203-686-1	> 10.0	200	250	835	1040	NF	200	250	NA	
TOSYLAMIDE/FORMALDEHYDE RESIN	1338-51-8	NA	NA	> 9.0	NA	NA	NF	NF	NF	NA	NA	NA	
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	> 5.0	400	500	983	1230	NF	400	500	2000	400TW
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	SA142000	229-937-9	≥ 3.0	NA	NA	NF	NF	NF	NA	NA	NA	
TRIPHENYL PHOSPHATE	115-86-6	TC8400000	NA	≥ 3.0	(3)	NA	(3)	NF	NF	(3)	NA	NA	
ETHYL TOSYLAMIDE	1077-56-1	NA	214-073-3	≥ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CAMPHOR	76-22-2	EX1225000	200-945-0	≥ 1.0	(2)	NE	2	NF	NF	(2)	NE	NE	
STEARALKONIUM BENTONITE	71011-24-0	NA	NA	≥ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	(15)DU ST
DIACETONE ALCOHOL	123-42-2	SA9100000	204-626-7	< 1.0	240	NA	238	NF	NF	240	1800	NA	
STEARALKONIUM HECTORITE	94891-33-5	NA	275-126-4	< 0.50	NA	NA	NF	NF	NF	NA	NA	NA	
BENZOPHENONE-1	131-56-6	DJ0700000	205-029-4	< 0.10	NA	NA	NF	NF	NF	NA	NA	NA	
CITRIC ACID	77-92-9	GE7350000	201-069-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIMETHICONE	9006-65-9	TY2000000	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	1	MAY COI	NTAIN ADDITIO	NAL INGR	EDIENTS	Š							
MICA	12001-26-2	VV8760000	310-127-6	≤ 1.0	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP
POLYETHYLENE TEREPHTHALATE	25038-59-9	NA	NA	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM SODIUM BOROSILICATE	65997-17-3	NA	266-046-0	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM ALUMINUM BOROSILICATE	65997-17-3	NA	266-046-0	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
ALUMINA	1344-28-1	BD1200000	215-691-6	≤ 1.0	(10)	NA	(5)	NF	NF	(15)	NA	NA	(5) DUST
SILICA	7631-86-9	NA	231-545-4	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
HYDROGENATED POLYISOBUTYLENE	68937-10-0	NA	NA	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
PALMITIC ACID	57-10-3	RT4550000	200-312-9	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIAMOND	7782-40-3	HL4158550	231-953-2	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
TIN OXIDE	18282-10-5	XQ4000000	242-159-0	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
SYNTHETIC FLUORPHLOGOPITE	12003-38-2	NA	234-426-5	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
SD ALCOHOL 40B	64-17-5	KQ6300000	200-578-6	≤ 1.0	1000	3000	1000	NF	NF	1000	3000	NE	
ADIPIC ACID / NEOPENTYL GLYCOL /TRIMELLTIC ANHYDRIDE COPOLYMER	28407-73-0	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
STYRENE/ACRYLATES COPOLYMER	NA	NA	NA	< 1.0									
CI 77120 (BARIUM SULFATE)	7727-43-7	CR0600000	231-784-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77163 (BISMUTH OXYCHLORIDE)	7787-59-9	EB2700000	232-122-7	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77891 (TITANIUM DIOXIDE)	13463-67-7	XR2275000	236-675-5	< 1.0	10	NA	NF	NF	NF	10	NA	NA	
		EO1400000	200-751-6	< 1.0	NA	NA	152	NF	NF	300			SKIN
N-BUTYL ALCOHOL	71-36-3	F() Zk(1700-751-6	L C 111			1 127		I IVE	300	NA	NA	

MATERIAL SAFETY DATA SHEET

Page 3 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards | MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

J. C	.OMFO31	IION & IN	GREDIENT	INFO	KIVIA	TION							
					EXPO	SURE LI	MITS IN	I AIR (mg/m ³)			
				AC	GIH		VOHSC			OSHA			
					pp	m		ppm			ppm		OTHER
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	
ETHYLENE/VA COPOLYMER	24937-78-8	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77491 (IRON OXIDES)	1309-37-1	NO740000	215-168-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77499 (IRON OXIDES)	1317-61-9	NA	215-277-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77510 (FERRIC FERROCYANIDE)	14038-43-8	LJ8200000	237-875-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 19140 (YELLOW 5)	1934-21-0	UQ6400000	217-699-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 47005 (YELLOW 10)	8004-92-0	GC5796000	305-897-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15850 (RED 6)	NA	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15850 (RED 7)	5858-81-1	QJ1975000	227-497-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 73360 (RED 30)	2379-74-0	NA	219-163-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15880 (RED 34)	6417-83-0	NA	229-142-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 42090 (BLUE1)	3844-45-9	BQ4725000	223-339-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77000 (ALUMINUM POWDER)	7429-90-5	BD0330000	231-072-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 75170 (GUANINE)	73-40-5	MF8260000	200-799-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 60725 (VIOLET 2)	81-48-1	CB7700000	201-353-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77007 (ULTRAMARINES)	1302-83-6	NA	215-111-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77266 (BLACK 2)	1333-86-4	NA	215-609-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	

4. FIRST AID MEASURES 4.1 First Ald: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the INGESTION: patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician. SKIN: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the effected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. INHALATION: Remove victim to fresh air at once. 4.2 Medical Conditions Aggravated by Exposure: **HEALTH** 1 None known. **FLAMMABILITY** 3 PHYSICAL HAZARDS 0 **PROTECTIVE EQUIPMENT** A **EYES**

 $()\cdot P \cdot T$

MATERIAL SAFETY DATA SHEET

Page 4 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

5. FIREFIGHTING MEASURES

Flashpoint & Method:

-4 °C (24 °F) estimated.

5.2 Autolanition Temperature:

NA

Flammability Limits: 5.3

Lower Explosive Limit (LEL):

NE

Upper Explosive Limit (UEL):

NE

Fire & Explosion Hazards: 5.4

WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.

Extinguishing Methods: 5.5

HazChem Code: 3YE

Hazard Identification Number: 33

CO₂, Halon, Dry Chemical, Foam

5.6 Firefighting Procedures:

> This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.

> First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



6. ACCIDENTAL RELEASE MEASURES

Spills: 6.1

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin greas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hyglene Practices:

> Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

7,2 Storage & Handling:

> Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from Incompatible materials (see Section 10).

7.3 Special Precautions:

> Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MATERIAL SAFETY DATA SHEET

MSDS Revision: 4.0

Page 5 of 10

MSDS-062G

MSDS Revision Date: 08/23/2011

1100		MSDS REVISION Dule. 06/23/2011						
		8. EXPOSURE CONTROLS & PERSONAL PROTECTION						
8.1	Ventilation & Engineering Conti							
	When working with largeyewash statlon, sink or	ge quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that ar I washbasin is available in case of exposure to eyes.						
8.2	Respiratory Protection:							
	protection authorized (protection is required under typical circumstances of use or handling. If necessary, use only respiratory per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate is provinces, E.C. member states, or Australia.						
8.3	Eye Protection:							
	Depending on the use Canadian standards, or	of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133 the European Standard EN166.						
8.4	Hand Protection:							
	If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routing industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.							
8.5		ction is required under typical circumstances of use and handling. If necessary, refer to appropriate standard mber states, or U.S. OSHA.						
		9. PHYSICAL & CHEMICAL PROPERTIES						
9.1	Donsity:	0.9998						
9.2	Bolling Point:	171 - 640°F						
9.3	Melting Point:							
		NE						
9.4	Evaporation Rate:	NA NA						
9.5	Vapor Pressure:	NA NA						
9.6	Molecular Welght:	NE						
9.7	Appearance & Color:	Viscous liquid, various colors						
9.8	Odor Threshold:	ND						
9.9	Salubility:	Insoluble						
9.10	рH	NA						
9.11	Viscosity:	> 1200 cPs						
9.12	Other Information:	NA						
		10. STABILITY & REACTIVITY						
10.1	Stability:							
	Stable under ambient c	onditions when stored properly (see Section 7, Storage and Handling).						
10.2	Hazardous Decomposition Prod							
	If exposed to extremely gases (e.g., CO, CO ₂).	r high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide						
10.3	Hazardous Polymerization:							
		o extremely high temperatures.						
10.4	Conditions to Avoid: This product is incompa strong bases (e.g., lye, p	tible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), o						
10.5	Incompatible Substances:	oolussioni nymonius j.						
	None known.							

$0.P \cdot I$

MATERIAL SAFETY DATA SHEET

Page 6 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards MSDS Revision: 4.0 MSDS Revision Date: 08/23/2011 11. TOXICOLOGICAL INFORMATION 11.1 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity: See Section 2.5 11.3 Chronic Toxicity: See Section 2.6 11.4 Suspected Carcinogen: This product contains Isopropyl Alcohol which is not carcinogenic to humans but is listed as a Group 3 carcinogen by the IARC. 11.5 Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. This product is not reported to produce embryotoxic effects in humans. This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.6 Irritancy of Product: See Section 2.3 Biological Exposure Indices: 11.7 11.8 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H₂O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life; There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

().P.T

MATERIAL SAFETY DATA SHEET

Page 7 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards | MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

49 CFR (GND): EXCEPTED QUANTITY (49 CFR §173.4a) (≤ 30 ml) CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L)

EXCEPTED QUANTITY (AIR SHIPPER § 4.1.2) (≤ 30 ml) CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L)

UN1263, PAINT RELATED MATERIAL, 3, II (> 0.5 L)

14.3 IMDG (OCN): EXCEPTED QUANTITY (2008 IMO § 3.5.1) (≤ 30 ml) UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L)

14.4 TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT RELATED MATERIAL, 3, II (> 1.0 L)

14.5 ADR/RID (EU): UN1263, PAINT RELATED MATERIAL, 3, II, ADR

> MEXICO (SCT): UN1263, PRODUCTOS PARA PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)

ADGR (AUS): UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (≤ 1.0 L)











15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

> This material contains Butyl Acetate, Ethyl Acetate, Isopropanol, and n-Butyl alcohol, which are subject to the reporing requirement of Section 131 of SARA Title III and 40 CFR Part 373

15.2 SARA Threshold Planning Quantity:

There are no specific Threshold Planning Quantities for the components of this product.

15.3 TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory.

15.4 CERCLA Reportable Quantity (RQ):

Butyl Acetate: 5000 lbs.; 2270 kg. Ethyl Acetate: 5000 lbs; 2270 kg. Acetone: 5000 lbs; 2270 kg.

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics)

15.6 Other Canadian Regulations:

> This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the Information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.



MATERIAL SAFETY DATA SHEET

Page 8 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

15. REGULATORY INFORMATION - continued

15.7 State Regulatory Information:

Ingredients in this mixture on found on the following state criteria lists:

California OSHA Hazardous Substances List **Delaware Air Quality Management List** Massachusetts Hazardous Substances List

Minnesota Hazardous Substances List

New Jersey Right to Know Hazardous Substances List New York List of Hazardous Substances Pennsylvania Hazardous Substances List

Washington Permissible Exposure Limits for Air Contaminants Wisconsin Hazardous Substances List

Butyl Acetate, Ethyl Acetate, Isopropanol, acetone

Butyl Acetate, Nitrocellulose, Ethyl Acetate

Butyl Acetate, Nitrocellulose, Ethyl Acetate, Isopropanol,

Camphor, Triphenyl Phosphate, acetone

Butyl Acetate, Ethyl Acetate, Isopropanol, Camphor,

Triphenyl Phosphate, acetone

Isopropanol, acetone

Butyl Acetate, Ethyl Acetate

Butyl Acetate, Ethyl Acetate, Isopropanol, Camphor,

Triphenyl Phosphate, acetone

Butyl Acetate, Ethyl Acetate, Isopropanol, Triphenyl Phosphate

Ethyl Acetate

15.8 67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC:

Ethyl Acetate: Flammable (F). R: 11-36/37/38 — Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, tumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.

Hazard Statements; H225 Highly flammable liquid and vapor. H319 Causes Serious Eye Irritation.

Precautionary Statements: P210Keep away from heat/sparks/open flames/hot surfaces - No Smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Butyl Acetate: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of Ignition - No smoking. Take precautionary measures against static discharges.

Hazard Statements: H225 Highly flammable liquid and vapor. H319 Causes Serious Eye Irritation.

Precautionary Statements: P210Keep away from heat/sparks/open flames/hot surfaces - No Smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Isopropanol: Flammable (F). R: 11-36/37 – Highly flammable. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 - Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

HAZCHEM CODE: 31Y1E Poison Schedule: None







MATERIAL SAFETY DATA SHEET

Page 9 of 10

MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 4.0

MSDS Revision Date: 08/23/2011

16. OTHER INFORMATION

16.1 Other Information:

EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. **KEEP OUT OF REACH OF CHILDREN**.

16.2 Terms & Definitions;

Please see last page of this MSDS.

16.3 Discialmer:

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/

 $O \cdot P \cdot I$

16.5 Prepared by:

ShipMate, Inc. PO Box 787

Sisters, OR 97759-0787 USA Phone: +1 (310) 370-3600

Fax: +1 (310) 370-5700

e-mail: shipmate@shipmate.com



-Dangerous Goods Training & Consulting

$0.P \cdot I$

MATERIAL SAFETY DATA SHEET

Page 10 of 10 MSDS-062G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58/EC & 1272/2008/EC Standards

MSDS Revision: 4.0

MSDS Revision Date:

08/03/2011

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number	
---------	----------------------------------	--

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists			
TLV	THE STATE OF THE S			
OSHA	U.S. Occupational Safety and Health Administration			
PEL	Permissible Exposure Limit			
IDLH	Immediately Danaerous to Life and Health			


FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose
heart has stopped receives manual chest compressions and breathing
to circulate blood and provide oxygen to the body.


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


0	Minimal Hazard	
1	Slight Hazard	
2 Moderate Hazard		
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:











G



Full Face Airline Hood/Mask Respirator or SCBA

Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Avallable
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maxlmum Llmit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autolgnition	Minimum temperature required to initiate combustion in air with no
Temperature	other source of Ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that
	wlll explode or lanite in the presence of an ignition source
VEL	Upper Explosive Limit - highest percent of vapor in air, by volume,
	that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minlmal Hazard
1.	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (sollds & liquids) which kills 50% of the exposed animals s						
LC₅o	Lethal concentration (gases) which kills 50% of the exposed animal						
ppm	Concentration expressed in parts of material per million parts						
TDIo	Lowest dose to cause a symptom						
TCLo	Lowest concentration to cause a symptom						
TDio, LDio, & LDo or	Lowest dose (or concentration) to cause lethal or toxic effects						
TC, TCo, LCio, & LCo							
IARC	International Agency for Research on Cancer						
NTP	National Toxicology Program						
RTECS	Realstry of Toxic Effects of Chemical Substances						
BCF	Bloconcentration Factor						
TLm	Medlan threshold limit						
log Kow or log Koc	Coefficient of Oll/Water Distribution						

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	U.S. Department of Transportation	
TC	Transport Canada	
EPA	U.S. Environmental Protection Agency	
DSL	Canadlan Domestic Substance Llst	
NDSL	Canadian Non-Domestic Substance List	
PSL	Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act	
EU	European Union (European Union Directive 67/548/EEC)	
WGK	Wassergefährdungsklassen (German Water Hazard Class)	

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0		(8)		(1)	®	€ 39	
A	В	С	D1	D2	D3	Е	F
Compressed	Flammable	Oxldizing	Toxic	Irritallon	Infectious	Сопозіче	Reactive

EC (67/548/EEC) INFORMATION:

		Mr.	*		X∕€		. *.
С	E	F	N	0	T+	XI	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Initiant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

		®	\Diamond			(1)		(4)
GHS01	GH\$02	GHS03	GHS04	GH505	GH\$06	GH\$07	GH\$08	GHS09
Explosive	Flammable	Oxldizer	Pressurized	Corrosive	Toxic	Harmful Irrikaling	Health Hazard	Environment