Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex

(877) 376-2839

Emergency: 800-255-3924

International Emergency: 813-248-0585

Balderson
RECT OCT 81 2007

# **Material Safety Data Sheet**

## 1. PRODUCT IDENTIFICATION

**Product Name:** 

HIGH TEMPERATURE SLEEVE RETAINER 6ML

Item No:

64000

**Product Type:** 

**Anaerobic** 

2. COMPOSITION/INFORMATION ON INGREDIENTS						
Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:			
DIMETHACRYLATE ESTER 27813-02-1	30-40	Not Listed	Not Listed			
POLYURETHANE METHACRYLATE RESIN 68400-67-9	5-20	Not Listed	Not Listed			
ACRYLIC ACID 79-10-7	1-10	2 ppm TWA	10 ppm TWA; 30 mg/m³ TWA			
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not Listed	Not Listed			
AROMATIC AMINE 609-72-3	<1	Not Listed	Not Listed			
ALKYL TOLUIDINE 613-48-9	<1	Not Listed	Not Listed			

## 3. HAZARDS IDENTIFICATION

Toxicity:

May cause eye and skin irritation. May cause nose, throat and respiratory irritation. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. High concentrations may cause central nervous

system (CNS) depression. May cause skin sensitization.

Primary Routes of Entry:

Signs and Symptoms of Exposure:

Eye and skin contact, ingestion, inhalation May cause redness to eyes and irritation to nasal passages. Repeated skin contact may cause allergic skin reactions. Ingestion may cause nausea and vomiting. Inhalation overexposure may cause irritation,

coughing and flu-like symptoms.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
ACRYLIC ACID	1-10		A4 - Not Classifiable	Group 3 Monograph 71,
79-10-7	1		as a Human	1999; Supplement 7, 1987;
			Carcinogen	Monograph 19, 1979

Medical Conditions Recognized as Being Aggravated by Exposure:

Preexisting pulmonary and dermatological disorders.

#### 4. FIRST AID MEASURES

Ingestion:

If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed.

Skin Contact:

Wash off with soap and water. If skin irritation persists, call a physician.

**Eye Contact:** 

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical

attention if irritation persists.

Obtain medical attention.

#### 5. FIRE FIGHTING MEASURES

Flash Point (°F/C):

Recommended Extinguishing Media: **Special Fire-Fighting Procedures:** Hazardous Products of Combustion: Unusual Fire/Explosion Hazards:

More than 200 degrees F. Method: TCC Water fog, carbon dioxide, foam, dry chemical.

Firefighters should wear self-contained breathing apparatus.

Irritating vapors, Oxides of carbon

None

## 5. FIRE FIGHTING MEASURES

Lower Explosive Limit: Upper Explosive Limit:

Not determined Not determined

## 6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until

disposal.

#### 7. HANDLING AND STORAGE

Storage:

Store below 100 degrees F.

Handling:

Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses

Skin:

Rubber or plastic gloves.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure

limits (or to the lowest feasible levels when limits have not been established) during the use of this

**Respiratory Protection:** 

An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the

applicable limits.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Green liquid

Odor:

**IRRITATING** 

**Boiling Point:** pH:

More than 150 degrees C. Does not apply

Solubility in Water:

Slight

**Specific Gravity:** 

1.1

VOC Content(Wt.%):

Not determined

Vapor Pressure:

Less than 10 mm Hg @ 25 degrees C.

Vapor Density (Air=1):

Heavier than air

**Evaporation Rate:** 

Not Determined

## 10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR.

Incompatabilities:

Strong oxidizers, free radical initiators, inert gases.

**Conditions to Avoid:** 

**Hazardous Products of Combustion:** 

Irritating vapors, Oxides of carbon

#### 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

#### 13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

**US EPA Waste Number:** 

NH - Not a RCRA Hazardous Waste Material

# 14. TRANSPORTATION INFORMATION

**DOT (49CFR 172)** 

## **Domestic Ground Transport**

**DOT Shipping Name:** 

Unrestricted

Hazard Class:

None

**UN/ID Number:** Marine Pollutant:

None None

IATA

**Proper Shipping Name:** 

Not regulated

# Product name HIGH TEMPERATURE SLEEVE RETAINER 6ML

Item No 64000

Class or Division:

None

**UN/NA Number:** 

None

<u>IMDG</u>

Proper Shipping: Hazard Class:

Unrestricted

None

UN Number:

None

# **15. REGULATORY INFORMATION**

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

ACRYLIC ACID, DIMETHYLBENZYL HYDROPEROXIDE

**CALIFORNIA PROP 65:** 

No California Prop 65 chemicals are known to be present.

**TSCA Inventory Status:** 

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

**Estimated NFPA Rating:** 

HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

Estimated HMIS Classification:

HEALTH 2, FLAMMABILILTY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:

Denise Boyd, Health and Safety Manager

Revision Date: 03/08/2005

Company:

Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision

Number: