

FLEX PRIME WHITE

PRODUCT NAME: FLEX PRIME WHITE  
PRODUCT CODE: 2333.

HMS CODES: H F R P  
1 0 0 E

FLEX PRIME WHITE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN AT THIS TIME.  
EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, APPLY ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN. EYE CONTACT: WASH EYES WITH CLEAN WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE  
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
VENTILATE AREA. PREVENT SKIN AND EYE CONTACT AND BREATHING OF VAPOR. CONTAIN AND REMOVE WITH INERT ABSORBENT.  
WASTE DISPOSAL METHOD

DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. ABSORB LARGES SPILLS WITH SAND, CLAY, OR DIATOMACEOUS EARTH. DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL DISPOSAL REQUIREMENTS.  
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 100 F.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.  
SECTION VIII - CONTROL MEASURES  
RESPIRATORY PROTECTION

DO NOT REQUIRE FOR BRUSH AND ROLL APPLICATION. FOR SPRAY APPLICATION, WEAR A PROPERLY FITTED F70SH/H9HA (TC-23C) APPROVED VAPOR/PARTICULATE RESPIRATOR UNTIL ALL VAPORS AND SPRAY MIST ARE EXHAUSTED.  
VENTILATION

PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW APPLICABLE OSHA PEL OR ACHN TLV  
OCCUPATIONAL EXPOSURE LIMITS. (SECTION IX)

PROTECTIVE GLOVES: IMPERVIOUS GLOVES ARE RECOMMENDED TO PREVENT SKIN CONTACT.  
EYE PROTECTION: USE CHEMICAL SAFETY GOGGLES OR FACE SHIELD TO PREVENT EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT  
COVERALLS, GLOVES AND HOOD ARE RECOMMENDED DURING SPRAY APPLICATION. PROTECTIVE CREAMS MAY BE USED FOR EASE OF CLEAN-UP, NOT FOR PROTECTION.

WORK/HYGIENIC PRACTICES: WASH HANDS BEFORE EATING OR USING THE RESTROOM.  
SECTION IX - DISCLAIMER  
AS OF THE DATE OF PREPARATION OF THIS DOCUMENT, THE FOREGOING INFORMATION IS BELIEVED TO BE ACCURATE AND IS PROVIDED IN GOOD FAITH.  
CONFEY WITH APPLICABLE FEDERAL AND STATE LAW(S). HOWEVER, NO WARRANTY OR REPRESENTATION WITH RESPECT TO SUCH INFORMATION IS INTENDED OR GIVEN.

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: PARKER PAINT  
ADDRESS: PO BOX 11047  
3003 SOUTH TACOMA WAY  
TACOMA, WA 98409  
EMERGENCY PHONE: 1-800-255-3924  
INFORMATION PHONE: 253-473-1122

DATE PRINTED: 10/29/97  
NAME OF PREPARER: J. BURWORTH

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ 20°C	WEIGHT PERCENT
ETHYLENE GLYCOL	107-21-1	.08	3

\* OSHA PEL: 50 PPM, ACHN TLV: 50 PPM

\* INDICATES CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLES III AND OF 40 CFR 371 ARE PRESENT.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOLLING RANGE: 212 Deg F  
SPECIFIC GRAVITY (H2O=1): 1.26

VAPOR DENSITY: LIGHTER THAN AIR  
EVAPORATION RATE: SLOWER THAN EITHER

SOLUBILITY IN WATER: DILUTABLE  
COATING V.O.C.: 1.02 lb/gal

APPEARANCE AND ODOR: AN OFF WHITE COLORED LIQUID WITH AMMONIACAL ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A  
METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 3.2  
UPPER: 15.2

OSHA FLAMMABILITY CLASS:  
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES  
FULL PROTECTIVE EQUIPMENT, INCLUDING A SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED TO PROTECT FIRE FIGHTERS FROM ANY HAZARDOUS COMBUSTION PRODUCTS.

UNUSUAL FIRE AND EXPLOSION HAZARDS  
WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

SECTION V - REACTIVITY DATA

STABILITY: STABLE  
CONDITIONS TO AVOID: DO NOT HEAT ABOVE 200 F.

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN AT THIS TIME.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE KNOWN AT THIS TIME.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
IRITATION OF HIGH CONCENTRATIONS OF VAPORS MAY CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT, AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
REPEATED LIQUID CONTACT MAY CAUSE SKIN IRRITATION AND DERMATITIS.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
NONE KNOWN AT THIS TIME.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
VOMITING CAN RESULT IN ASPIRATION OF MATERIAL INTO

THE LUNGS WHICH CAN CAUSE CHEMICAL PNEUMONITIS.

HEALTH HAZARDS (ACUTE AND CHRONIC)  
ACUTE: (SHORT TERM) OVER EXPOSURE MAY CAUSE HEADACHE, NAUSEA, SKIN AND EYE IRRITATION. CHRONIC: (LONG TERM) UNPROTECTED OVER

EXPOSURE TO MISTS FROM SPRAY APPLICATION MAY CAUSE LUNG DISEASE (SILICOSIS).

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO