

Revision Number: 005.0 Issue date: 08/04/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

Loctite(R) Extend(R) Rust Treatment IDH number: Product name: 234928 Product type: Rust converter Item number: 30539 Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Region: **United States** Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: EXTREMELY FLAMMABLE AEROSOL.

HARMFUL IF SWALLOWED.

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	1
ACUTE TOXICITY ORAL	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3





#### **Precautionary Statements**

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye

protection, and face protection.

If SWALLOWED: Immediately call poison control or physician if you feel unwell. IF Response:

SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or

physician. Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage:

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents and/or container according to Federal, State/Provincial and local Disposal:

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
2-Butoxyethanol	111-76-2	30 - 60
Acetone	67-64-1	30 - 60
Butyral resin	Proprietary	5 - 10
Formic acid	64-18-6	5 - 10
3,4,5-Trihydroxybenzoic acid	149-91-7	0.1 - 1

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Seek medical advice.

Skin contact: Remove contaminated clothing and footwear. Wash with soap and water. If

symptoms develop and persist, get medical attention. Wash clothing before

reuse.

Eye contact: Immediately flush eyes with water for at least 15 minutes, while holding

eyelids open. Seek medical attention at once.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a

doctor.

Symptoms: See Section 11.

IDH number: 234928

## 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide. Dry chemical. foam

Special firefighting procedures: Use water spray to keep fire exposed containers cool and disperse vapors.

Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat. Vapours may accumulate in low or confined areas, travel

considerable distance to source of ignition, and flash back.

Hazardous combustion products: Oxides of carbon. Hydrocarbons

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system. Do not let product

enter drains. Absorb spill with inert material. Shovel material into appropriate

container for disposal.

Clean-up methods: Absorb the spilled material with an inert absorbent (nonflammable) material.

### 7. HANDLING AND STORAGE

**Handling:** Avoid breathing mists or aerosols of this product. Keep away from sources of

ignition - no smoking. Avoid contact with eyes, skin and clothing.

Storage: Store in a cool, dry area. Keep containers closed when not in use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m3) PEL (SKIN)	None	None
Acetone	750 ppm STEL 500 ppm TWA	1,000 ppm (2,400 mg/m3) PEL	None	None
Butyral resin	None	None	None	None
Formic acid	5 ppm TWA 10 ppm STEL	5 ppm (9 mg/m3) PEL	None	None
3,4,5-Trihydroxybenzoic acid	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol, Liquid Translucent Color: Odor: Acetone Odor threshold: Not available. pH: Not available. Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: 1.0000 Vapor density: Not available.

Flash point: < -17.7 °C (< 0.14 °F); This product exhibits flashback when tested for flame

extension.

Flammable/Explosive limits - lower: 1.1 %
Flammable/Explosive limits - upper: 57 %

IDH number: 234928

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

Not available.

Not available.

Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 234928

Irritating organic vapours. Oxides of carbon.

**Incompatible materials:** Acids and bases. Oxidizing agents.

Reactivity: Not available.

**Conditions to avoid:** Keep away from heat, spark and flame.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

Inhalation: Vapours may cause drowsiness and dizziness.

**Skin contact:** Causes skin burns.

**Eye contact:** Causes serious eye damage. **Ingestion:** Harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
2-Butoxyethanol	Oral LD50 (RAT) = 560 mg/kg Oral LD50 (RABBIT) = 0.32 g/kg Oral LD50 (RAT) = 1.48 g/kg Dermal LD50 (RABBIT) = 400 mg/kg Inhalation LC50 (RAT, 4 h) = 486 ppm Inhalation LC50 (RAT, 4 h) = 450 ppm	Blood, Central nervous system, Irritant, Kidney, Liver	
Acetone	Oral LD50 (RABBIT) = 5,340 mg/kg Oral LD50 (RAT) = 5,800 mg/kg Oral LD50 (RAT) = 9,800 mg/kg Dermal LD50 (RABBIT) = 20,000 mg/kg Inhalation LC50 (RAT, 8 h) = 50.1 mg/l Inhalation LC50 (RAT, 4 h) = 76 mg/l	Blood, Central nervous system, Irritant, Reproductive	
Butyral resin	None	No Records	
Formic acid	Oral LD50 (RAT) = 730 mg/kg Inhalation LC50 (RAT, 15 min) = 15 mg/l Inhalation LC50 (RAT, 4 h) = 7.4 mg/l	Central nervous system, Corrosive, Irritant, Kidney, Metabolic	
3,4,5-Trihydroxybenzoic acid	Oral LD50 (RABBIT) = 5.0 g/kg	Irritant, Central nervous system	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Butoxyethanol	No	No	No
Acetone	No	No	No
Butyral resin	No	No	No
Formic acid	No	No	No
3,4,5-Trihydroxybenzoic acid	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Not available.

Hazardous waste number: D001: Ignitable.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols, flammable

Hazard class or division:

Identification number:

Packing group:

DOT Hazardous Substance(s):

2.1

UN 1950

None

Acetone

International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, flammable

Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Additional information: IMDG-Code: Segregation group 1- Acids

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Sudden Release

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). 2-Butoxyethanol (CAS# 111-76-2).

CERCLA Reportable quantity: Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)

Formic acid (CAS# 64-18-6) 5,000 lbs. (2,270 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

IDH number: 234928

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

**Issue date:** 08/04/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.