

and 40 CFR part 372.

The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont Page 1 Material Safety Data Sheet "FREON" 114 3038FR Revised 7-JAN-1997 CHEMICAL PRODUCT/COMPANY IDENTIFICATION Material Identification "FREON" is a registered trademark of DuPont. Corporate MSDS Number : DU001061 CAS Number : 76-14-2 Formula : CClF2CClF2 Tradenames and Synonyms DICHLOROTETRAFLUOROETHANE DICHLOROTETRAFLUOROETHANE, 1,2-ETHANE, 1,2-DICHLOROTETRAFLUORO F-114 **REFRIGERANT 114** Company Identification MANUFACTURER/DISTRIBUTOR DuPont Fluoroproducts 1007 Market Street Wilmington, DE 19898 PHONE NUMBERS Product Information : 1-800-441-7515 (outside the U.S. 302-774-1000) Transport Emergency : CHEMTREC 1-800-424-9300 (outside U.S. 703 - 527 - 3887) Medical Emergency : 1-800-441-3637 (outside the U.S. 302-774-1000) COMPOSITION/INFORMATION ON INGREDIENTS Components Material CAS Number *1,2-DICHLORO-1,1,2,2-TETRAFLUOROETHANE 76-14-2 100 ("FREON" 114) * Disclosure as a toxic chemical is required under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986

DuPont Material Safety Data Sheet

HAZARDS IDENTIFICATION

Potential Health Effects

3038FR

Inhalation of high concentrations of vapor is harmful and may cause heart irregularities, unconsciousness or death. Intentional misuse or deliberate inhalation may cause death without warning. Vapor reduces oxygen available for breathing and is heavier than air. Liquid contact can cause frostbite.

HUMAN HEALTH EFFECTS:

Overexposure by skin or eye contact may include skin irritation with discomfort or rash; or eye irritation with discomfort, tearing, or blurring of vision. Contact with liquid may cause frostbite. Overexposure by inhalation of the vapors may cause nonspecific discomfort such as nausea, headache, or weakness; temporary alteration of the heart's electrical activity with irregular pulse, palpitations, or inadequate circulation.

Individuals with preexisting diseases of the central nervous or cardiovascular system may have increased susceptibility to the toxicity of excessive exposures.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES

First Aid

INHALATION

Immediately remove to fresh air. Keep persons calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush with water. Treat for frostbite if necessary. Get medical attention if irritation is present.

EYE CONTACT

Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

3038FR DuPont Page 3 Material Safety Data Sheet (FIRST AID MEASURES - Continued) Ingestion is not considered a potential route of exposure. Notes to Physicians Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution in situations of emergency life support. FIRE FIGHTING MEASURES Flammable Properties Flash Point : Will not burn : TOC Method Flammable limits in Air, % by Volume LEL : Not applicable UEL : Not applicable : Not determined Autoignition : 593 C (1099 F) Autodecomposition Fire and Explosion Hazards: Cylinders are equipped with pressure and temperature relief devices but still may rupture under fire conditions. Decomposition may occur. Extinguishing Media As appropriate for combustibles in area. Fire Fighting Instructions Self-contained breathing apparatus (SCBA) is required if cylinders rupture or release contents under fire conditions. Use water spray or fog to cool containers. ACCIDENTAL RELEASE MEASURES Safequards (Personnel) NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up. Accidental Release Measures Ventilate area, especially low places where heavy vapors might collect. Remove open flames. Use self-contained breathing apparatus (SCBA) in case of large spills. Comply with Federal, State, and local regulations on reporting releases.

3038FR DuPont Page 4 Material Safety Data Sheet ______ HANDLING AND STORAGE Handling (Personnel) Avoid breathing vapors and contact of liquid with skin or eyes. Use with sufficient ventilation to keep employee exposure below recommended limits. Storage Clean, dry area. Do not heat above 125 deg F. _________________________ EXPOSURE CONTROLS/PERSONAL PROTECTION ______ Engineering Controls Normal ventilation for standard manufacturing procedures is generally adequate. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places. Personal Protective Equipment Impervious gloves should be used if liquid contact with skin is possible. Chemical splash goggles should be available for use as needed to prevent liquid contact with the eyes. Under normal manufacturing conditions, no respiratory protection is required when using this product. Self-contained breathing apparatus (SCBA) is required if a large release occurs. Exposure Guidelines Exposure Limits "FREON" 114 : 1,000 ppm, 7,000 mg/m3, 8 Hr. TWA : 1,000 ppm, 6,990 mg/m3, 8 Hr. TWA, A4 PEL (OSHA) TLV (ACGIH) AEL * (DuPont) : None Established * AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence. _______ PHYSICAL AND CHEMICAL PROPERTIES ______ Physical Data

 Boiling Point
 : 4 C (39 F)

 Vapor Pressure
 : 31 psia @ 25 C (77 F) (77 deg F)

 Vapor Density
 : 6.2 (Air=1.0) @ 25 C (77 F)

 % Volatiles
 : 100 WT%

 Evaporation Rate
 : >1 (CCl4=1.0)

 Solubility in Water
 : 0.013 WT% @ 25 C (77 F)

3038FR DuPont Page 5 Material Safety Data Sheet (PHYSICAL AND CHEMICAL PROPERTIES - Continued) Odor : Slight ethereal Form : Liquefied gas Color : Clear, colorless Density : 1.46 g/cm3 @ 25 C (77 F) - Liquid C (77 deg F) - Liquid STABILITY AND REACTIVITY Chemical Stability Material is stable. However, avoid open flames and high temperatures. Incompatibility with Other Materials Incompatible with alkali or alkaline earth metals- powdered Al, Zn, Be, etc. Decomposition Decomposition products are hazardous. "FREON" 114 can decompose at high temperatures (open flames, glowing metal surfaces, etc.) forming hydrochloric and hydrofluoric acids, and possibly carbonyl halides. Polymerization Polymerization will not occur. Other Hazards Decomposition : Decomposition products are hazardous. "FREON" 114 can decompose at high temperatures (open flames, glowing metal surfaces, etc.) forming hydrochloric and hydrofluoric acids, and possibly carbonyl halides. TOXICOLOGICAL INFORMATION Animal Data Inhalation 0.5-Hour LC50: 720,000 ppm in rats Oral ALD : >2250 mg/kg in rats

The compound is a mild skin irritant, is a mild eye irritant, and is untested for animal sensitization. Toxic effects described in animals from exposures by inhalation or ingestion include central nervous system effects, cardiac sensitization, respiratory effects, and liver effects. A limited study with mice exposed for 23 months to a mixture of chlorofluorocarbons including 250,000 ppm of "FREON" 114

```
Page 6
 3038FR
                      DuPont
               Material Safety Data Sheet
           (TOXICOLOGICAL INFORMATION - Continued)
   demonstrated no evidence of carcinogenic activity. No
   animal test reports are available to define embryotoxic, or
   reproductive hazards. Tests in bacterial or mammalian cell
   cultures demonstrate no mutagenic activity.
 ECOLOGICAL INFORMATION
 _____
 Ecotoxicological Information
   Aquatic Toxicity
   96-hour LC50, killifish: 45 ppm
   ______
 DISPOSAL CONSIDERATIONS
 ______
 Waste Disposal
   Comply with Federal, State, and local regulations. Reclaim
   by distillation or remove to a licensed waste disposal
   facility.
 TRANSPORTATION INFORMATION
 # Shipping Information
   DOT/IMO/IATA
    Proper
   Shipping Name : 1,2-DICHLORO-1,1,2,2-TETRAFLUOROETHANE
Hazard Class : 2.2
                : 1958
    Un No.
    Shipping Label
               : Nonflammable Gas
   Shipping Containers:
    Tank Cars
    Tank Trucks
    Cylinders
 REGULATORY INFORMATION
 ______
 U.S. Federal Regulations
   TSCA Inventory Status : Reported/Included.
   TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312
   Acute
          : Үев
   Chronic : No
Fire : No
   Reactivity : No
```

DuPont Page 7 Material Safety Data Sheet (REGULATORY INFORMATION - Continued) : No Pressure LISTS: Extremely Hazardous Substance -No CERCLA Hazardous Substance -No Toxic Chemicals -Yes OTHER INFORMATION NFPA, NPCA-HMIS NPCA-HMIS Rating Health : 1 Flammability : 0 Reactivity : 1 Personal Protection rating to be supplied by user depending on use conditions. The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Responsibility for MSDS : MSDS Coordinator > : DuPont Fluoroproducts Address : Wilmington, DE 19898 Telephone : (800) 441-7515 # Indicates updated section. This information is based upon technical information believed to be

reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS

3038FR

(

· magazine ·